



Technical Data:

| | |
|--|--------------------------|
| Case Material..... | PA black |
| Switch Lever Material..... | PA black |
| Min. Insulation Resistance..... | 100MΩ |
| Dielectric Withstanding Voltage..... | 1050V-1min |
| Max. Contact Drop during Resistive Load..... | 150mV |
| Voltage..... | to 32VDC |
| Duty Rating..... | 400A |
| Overload..... | 1200A-4min |
| | 1600A-1.5min |
| | 2000A-10sec |
| Sealing..... | IP 67 / IEC 529 |
| Vibration..... | 4G / 50-2000Hz |
| Shock G-Level..... | 6G / 11ms |
| Weight..... | 360g / 0.8 Pound |
| Temperature Range..... | -40°C to +85°C |
| Wire Section (At Nominal Load)..... | min. 240 mm ² |
| Switch Lever..... | not removeable |
| Torque (Main Terminals)..... | 15-20 Nm |

| | | | | | | |
|-------|------------|-------|---------------------------------------|-------|--|-------------|
| | Date | Name | mm | Scale |  Elektrotechnik - GmbH & Co KG D - 72218 Wildberg | Drawing No: |
| Drawn | 26.06.2003 | Mielk | ← | 1:2 | | 35-402 |
| Check | 24.05.2005 | Mielk | General Tolerances DIN ISO 2768 mK | | | NSN.: |