


T-1^{3/4}

SUB-MINIATURE LAMPS

*QPL - 6363 CERTIFIED BY THE DEPARTMENT OF DEFENSE.



LINE NO.	VOLTS	AMPS	MSCP	LIFE	FILAMENT	* Midget Flanged Base
1						
2	1.35	.060	.010N	500	C-2R	331
3	2.47	.300	.450	30	C-2R	251
4	2.50	.200	.220	500	C-2R	368
5	2.50	.350	.210	10,000	C-2R	268
6	2.50	.400	.550	30	C-2R	343
7	2.70	.060	.040	6,000	C-2R	338
8	3.00	.015	.003N	10,000	C-6	375
9	3.00	.030	.020N	1,800	C-6	7329
10	4.50	.120	.050	25,000	C-2V	7331
11						
12	5.00	.017	.018N	8,000	C-2R	8950
13	5.00	.060	.050	100,000	C-2R	7333
14	5.00	.060	.150	5,000	C-2R	3150 (M6363/8-1)
15	5.00	.060	.030	100,000	C-2R	7332
16	5.00	.115	.150	40,000	C-2R	7335
17	5.00	.190	.450	1,000	C-2R	7334
18	6.00	.040	.030	10,000	C-2V	345
19	6.00	.200	.600	1,000	C-2R	328 (M6363/8-2)
20	6.00	.200	.100	50,000	C-2F	7336
21						
22						
23	6.30	.040	.020N	50,000	C-2V	380
24	6.30	.075	.220	500	C-2R	377
25	6.30	.150	.450	3,000	C-2R	350
26	6.30	.200	.400	50,000	C-2F	381 (M6363/8-3)
27	6.30	.200	.550	3,000	C-2R	349
28	10.00	.014	.002N	10,000	C-2F	344
29	10.00	.040	.080	3,000	C-2F	367
30	10.00	.040	.080	5,000	C-2F	367X
31						
32	11.00	.022	.030	10,000	C-2F	7338
33	12.00	.040	.120	10,000	C-2F	394
34	14.00	.080	.300	50,000	C-2F	382
35	14.00	.080	.500	1,500	C-2F	330
36	14.00	.080	.300	40,000	C-2F	
37	14.00	.100	.500	10,000	C-2F	
38	14.00	.100	.500	10,000	C-2F	8918 (M6363/8-4)
39	18.00	.040	.150	10,000	C-2F	370
40	22.00	.040	.300	2,000	C-2F	459
41						
42	24.00	.050	.500	2,000	C-2F	8176
43	28.00	.024	.150	16,000	C-2F	6034
44	28.00	.040	.340	7,000	C-2F	327 (M6363/8-5)
45	28.00	.040	.300	25,000	C-2F	387 (M6363/8-7)
46	28.00	.040	.200	50,000	C-2F	385 (M6363/8-6)
47	28.00	.060	.340	25,000	C-2F	376
48	28.00	.065	.650	5,000	C-2F	7341
49	48.00	.025	.200	5,000	CC-2F	6848
50	60.00	.020	.250	5,000	CC-2F	—