4	3	2	1	
		ZONE REV. REVISION DESCRIPTION	ECN NO. DATE	
		B ADD TABLE WITH BUTTON COLORS; PD	ECO-074856 29-MAR-2012	
D				D
2X FLATS FOR 9/16 WRENCH				
		PERFORMANCE CHARACTERISTICS DEFINATIONS AND TEST CRITERIA PER SENSATA TECHNOLOGIES DRAWING 76115		
		PRETRAVEL.040 MIN.TOTAL TRAVEL.050 MIN.ACTUATION FORCE40 OZ. MAX.		
C	160	LIFE AT RATED LOAD 25,000 CYCLES AMBIENT TEMPERATURE RANGE -65 F TO +275 F		C
\bullet	460 456	VOLTAGE DROP AT 1 AMP.040 VOLTSSEALCLASS 5 HERMETICCURRENT CAPACITY3 AMPS RESISTIVE		
		SHOCK RESISTANCE 200 G'S VIBRATION RESISTANCE (55-2000 HZ) 65 G'S		
.104	.284 .254	DIELECTRIC STRENGTH 800 VRMS TERM TO TERM 1000 VRMS TERM TO CASE		
.405				
.395	5/8-24 UNEF-2A THREAD			
B				В
		10AT501-03 GREY BUTTON		
	. 742	10AT501-02BLACK BUTTON10AT501-01RED BUTTON		
	\$\vert^{.742}_{.738}	PART NO. BUTTON		
		FOR REFERENCE ONLY, CHECK LATEST REVISION BEFORE USE. PARTS MADE TO THIS PRINT MUST CONFORM TO E9898 REV. E.	529 PLEASANT STREET	
		DRAWN G.LAPATI DATE 01-FEB-2012 DRAWN G.LAPATI DATE 01-FEB-2012 DRAWN G.LAPATI DATE 01-FEB-2012 DRAWN G.LAPATI DRAWN G.LAPATI DRAWN G.LAPATI DRAWN G.LAPATI DRAWN G.LAPATI DRAWN G.LAPATI DRAWN G.LAPATI DRAWN G.LAPATI DRAWN G.LAPATI DRAWN G.LAPATI DRAWN G.LAPATI DRAWN G.LAPATI DRAWN G.LAPATI DRAWN G.LAPATI DRAWN G.LAPATI DRAWN G.LAPATI DRAWN G.LAPATI DRAWN G.LAPATI G.LAP		
		ENGINEER OR AGAINST THE INTERESTS OF ANY OF ITS AFFILIATED		-
		J.FOURNER DATE 01-FEB-2012 INTERPRET DIMENSIONING AND TOLERANCING PER ASME Y14.5-2009. UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES.	SPDT HERMETIC JSH BUTTON SWITCH	
A HARDWARE	E INCLUDED: LOCKWASHER		IVELOPE DRAWING	A
		DATE 01-FEB-2012 SIZE DWG		
		APPROVED W.BENTLEY DATE 01-FEB-2012 DO NOT SCALE DRAWING DO NOT SCALE PROJECTION B SCALE 2:	10AT501B1SOLIDWORKSSHEET 1 OF 1	-
4	3	2 <u>DRAWING</u> <u>JORALE 2.</u>	1]